

冷凝器简易选型表

制热功率 (KW)	制热功率 (HP)	35℃冷凝水25-30℃				40℃冷凝水30-35℃				50℃冷凝水40-45℃				60℃冷凝水50-55℃				水流量 t/h
		板换型号				板换型号				板换型号				板换型号				
		HU26	HU50	HU95B	HU210	HU26	HU50	HU95B	HU210	HU26	HU50	HU95B	HU210	HU26	HU50	HU95B	HU210	
2.5	1.0	12				12				12				14				0.43
3.8	1.5	16				16				18				18				0.60
5.0	2.0	18				20				22				22				0.86
7.5	3.0	26				28				30				32				1.28
10.0	4.0	34				36				40				42				1.71
12.5	5.0	42	18			46	18			48	20			52	20			2.14
15.0	6.0	48	22			54	22			58	24			62	24			2.58
17.5	7.0	56	24			62	24			66	26				28			3.00
20.0	8.0	64	26				26				28				32			3.43
22.5	9.0		28				30				32				34			3.85
25.0	10.0		30				32				36				38			4.28
27.5	11.0		34				36				38				42			4.71
30.0	12.0		36				38				42				46			5.14
32.5	13.0		40				40				44				48			5.57
35.0	14.0		42				44				48				52			6.01
37.5	15.0		46				48				50				56			6.42
40.0	16.0		48				50				54				60	36		6.85
42.5	17.0		50				52				58				64	38		7.28
45.0	18.0		52				56				60	38			66	42		7.71
47.5	19.0		56	36			58	36			64	40				44		8.14
50.0	20.0		58	38			60	38				42				46		8.56
62.5	25.0			46				48				52				56		10.70
75.0	30.0			54				56				60				66		12.86
87.5	35.0			62				64				70				76		15.00
100.0	40.0			70				74				80				88		17.13
125.0	50.0			88				92				100	52			108	56	21.41
150.0	60.0			104	54			108	56			118	62			128	66	25.69
175.0	70.0			120	62			126	66			138	70			150	78	29.97
200.0	80.0			138	70			144	74			156	80				88	34.25
225.0	90.0				78								90				98	38.52
250.0	100.0				88				90				100				108	42.80