

蒸发器简易选型表

制热功率 (KW)	制热功率 (HP)	2℃蒸发水12-7℃				3℃蒸发水12-7℃				5℃蒸发水15-10℃				10℃蒸发水20-15℃				水流量 t/h
		板换型号				板换型号				板换型号				板换型号				
		HU26	HU50D	HU95	HU210	HU26	HU50D	HU95	HU210	HU26	HU50D	HU95	HU210	HU26	HU50D	HU95	HU210	
2.5	1.0	16				18				14				14				0.43
3.8	1.5	20				22				18				18				0.60
5.0	2.0	24				28				24				24				0.86
7.5	3.0	34				40				34				32				1.28
10.0	4.0	44				52	26			42				40				1.71
12.5	5.0	54	26			64	30			52	26			50	24			2.14
15.0	6.0	64	30				36			62	30			58	28			2.58
17.5	7.0		34				40				34				32			3.00
20.0	8.0		38				46				38				36			3.43
22.5	9.0		42				50				42				38			3.85
25.0	10.0		46				56				44				42			4.28
27.5	11.0		50				60	36			50				46			4.71
30.0	12.0		56	34			66	38			52	34			50	30		5.14
32.5	13.0		60	36				42			58	36			54	32		5.57
35.0	14.0		64	40				44			62	38			58	36		6.01
37.5	15.0			42				48				40			62	38		6.42
40.0	16.0			44				50				44				40		6.85
42.5	17.0			46				54				46				42		7.28
45.0	18.0			48				56				48				44		7.71
47.5	19.0			52				60				50				46		8.14
50.0	20.0			54				62				54				48		8.56
62.5	25.0			66				78				64				60		10.70
75.0	30.0			80				94				76				72		12.86
87.5	35.0			94				110	60			88				82		15.00
100.0	40.0			108	58			124	68			100	56			96	52	17.13
125.0	50.0			134	70			158	82			126	68			118	64	21.41
150.0	60.0			162	84			194	100			154	80			144	76	25.69
175.0	70.0			190	98				116			184	94			170	88	29.97
200.0	80.0			220	112				134			214	106			198	100	34.25
225.0	90.0				126				152				122				114	38.52
250.0	100.0				140				168				134				128	42.80